

AC Portable/Wallbox EV Charger


NACS connector



Product Features :

- Highly compatible with new energy vehicle charging interfaces/protocols.
- Multi-intelligent detection: real-time voltage/current monitoring, precise power calculation & safety protection.
- 1.9" LCD display: standby/charging/fault status & params Authorization modes: plug-and-charge, APP/button scheduling.
- Charging modes: auto-full, timed charging.
- 4-level adjustable current with memory (auto-restores last gear on power-up).
- Remote O&M platform: health diagnosis, fault (early warning), OTA upgrades (reduces costs).
- Product certified with ETL&CETL, FCC, TÜVmark

Applications :

- Suitable for home and industrial use.
- Suitable for carrying in the car, traveling charging, and emergency charging.

Specifications :

Item	ZA06-U007KXX-X001	ZA06-U09K6XX-X001	ZA06-E011KXX-X001	ZA06-E022KXX-X001
Input Voltage	AC240V±15%		AC400V±10%	
Input Frequency	60Hz±1Hz		50Hz±1Hz	
Output Power	7kW	9.6kW	11kW	22kW
Current	32A	40A	16A (3-phase)	32A (3-phase)
Current Range	16A-20A-24A-32A	16A-24A-32A-40A	8A-10A-13A-16A	16A-20A-24A-32A
Display Size	1.9 inches			
Communication	WI FI&Bluetooth			
Gun Cable Length	5m/7m/7.5m			
Temperature /Humidity	-30 ~ +40°C/5%~95%RH			
Protection	IP66			
Appearance Size	Length 420mm; Diameter 80mm			
Product Weight	<5.8KG			
Leakage Protection	Type A+ DC6mA(EU)/CCID20(US)			